

WEBANCOR.COM

WEB & CORE TECHNOLOGIES INC.
7311A KIMBEL ST.

Mississauga, Ont. L4T 3M6
CANADA

PH 905-677-9476 FAX 905-677-7841 TOLL-FREE 1-888-421-1405
<http://www.webancor.com> TOLL FREE FAX 1-888-414-4428
<http://www.airshafts.com>

WEBANCOR is a registered TRADE MARK

NOTICE

AIR SHAFT AND AIR CHUCK VALVES

A THREAD SEALING COMPOUND must be used to seal the threads in these valves.

TEFLON TAPE IS NOT RECOMMENDED for valve application, as the tape will string off and blow back inside the valve preventing the o'ring from sealing properly.

Air shafts and chucks should be operated at about **85-90 psi (6 Bar)** and standard taper threads will not seal properly without excessive tightening. Excessive tightening will cause the brass body to distort causing leaks.

A good quality thread compound comes in tubes, and is available at any industrial supply house. Tubes can be ordered from **WEBANCOR** if necessary. This compound lubricates the thread when threading the valve into the body and seals without having to exert unnecessary force on the valve.

DO NOT OVERTIGHTEN THE VALVE.

DO NOT USE SHARP OBJECTS TO RELEASE AIR FROM THE VALVES

USE CAUTION WITH COMPRESSED AIR

WEB & CORE TECHNOLOGIES INC.
CORE SHAFTS, CHUCKS, BOWED ROLLS, and IDLER ROLLS
www.webancor.com
Sales offices in Canada,USA , Europe and Indonesia